




12±0.2 L 12±0.2



P1



P2

## PIN OUT

P1

P2

1

1 RED

2

2 WHITE

3

3 GREEN

4

4 BLACK

SHELL

Braid

SHELL

### MATERIAL (ROHS COMPLIANT):

#### 1. FOUR TYPES CABLE OPTIONAL

[ 28AWG(7/0.12MM BC) X 1P + 28AWG(7/0.12MM BC) X 2C] + AL/POLY FOIL + BRAID(3/16/0.12MM AL-MG) + JACKET PVC, OD: 3.8MM

MARKING: USB 2.0 VERIFIED FULLY RATED 30V 80°C RoHS COMPLIANT

#### 2. CONNECTOR:

USB A MALE, BLACK INSULATION, 3U" GOLD PLATED CONTACT, NICKEL PLATED SHELL  
USB B MALE, BLACK INSULATION, 3U" GOLD PLATED CONTACT, NICKEL PLATED SHELL

#### 3. MOULD:

P1/P2: PE INNER MOULD, PVC OUTER MOULD IN BLACK COLOR

Itemref	Quantity	Title/Name, designation, material, dimension etc			Article No./Reference	
Designed by	Checked by	Approved by - date	File name	Date	Scale	
		DEC.15,2008	USB	DEC.15,2008	FREE	
USB A M / USB B M(28AWG)				Edition	Sheet	
				1	1/1	